

SYMPHONI LX WALL BASE

Alarm devices
Product Datasheet

EN 54-23 Coverage Reference: W-2.4-7.5

Features

- Ultra low current consumption
- 7.5m coverage (135m³)
- 0.5 or 1Hz flash rate
- IP21C protection
- Use where current consumption is a key consideration
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to reduce current consumption
- External use in areas of high humidity

Description / Application

The Symphoni LX Wall base can be used in combination with any standard Symphoni sounder. Its durable design ensures reliability and its high sound output makes it suitable for open areas or where there is higher than normal background noise.

The base is non-addressable. 3 optional sounders (see part numbers) can be mounted onto the base.



The photo shows the complete product, including both the base and optional sounder.

Product Name	Part number	Description
Symphoni LX Wall Base	116-4340-007.0004	Symphoni LX Wall Base
Optional sounders:		
Addressable sounder	116-BBR-230	Addressable
Addressable sounder	116-BBR-200	Addressable
Alarm Symphoni RED SY/R IP42	116-7770-009.0020	Conventional

Technical specifications (for complete product; wall base and sounder)	
Mounting Type	Wall
Voltage	18 – 28Vdc (Fire Use)
Current	15 – 30mA dependent on setting (Sounder and; tone 3)
Coverage (y)	7.5m (Switchable to 2.5m)
Mounting Height (x)	2.4m (max)
Coverage Volume Code	W-2.4-7.5
Coverage Volume	135 m ³ (15m ³)
Flash Rate	1Hz (Switchable)
Operating Temperature	-25°C - +70°C
Monitoring	Reverse Polarity
Protection	IP21C
Weight	200g
Body Colour	Red
Flash Colour	Red
Sound Output	100dB(A) (Typical tone 29 – Symphoni)

Dimension Drawing (complete product; wall base and sounder)

